



4G



GK310 Ultra-slim GPS Tracker

Available on the App Store

App for Android



HD touch screen

Clearly show detailed information; more practical and useful.



GPS+LBS positioning

Allow the location to be pinpointed accurately and rapidly.



SOS call & Speed-dial

Thumb sized button allowing urgent call during an emergency case.



Two-way talk

With MIC and speaker, it realizes two-way communication.



Listen-in

Listen to the surroundings by sending a text message.



Multiple alerts

Receive notices for low battery, shutdown, SIM card replacement.



Children protection



Lone worker protection



Elderly people safety

GK310 GPS tracker

Category	Item	Specification
FDD LTE	Band	Band 1,Band 2,Band 3,Band 4,Band 5, Band7,Band8, Band 19
WCDMA	WCDMA	850/900/1900/2100MHz
GSM	GSM frequency	850/900/1800/1900MHz
	GPRS	Class 12, TCP/IP
	Memory	512MB RAM+8GB ROM
	Phase error	RMSPE<5,PPE<20
	Max output	GSM850/GSM900:33±3dBm GSM1800/GSM1900:30±3dBm
	Max frequency error	±0.1ppm
GPS	GPS chipset	MT6737
	Frequency	L1,1575.42MHz C/A code
	GPS channel	66
	Location accuracy	<10 meters
	Tracking sensitivity	-165dBm
	Acquisition sensitivity	-148dBm
	TTF (open sky)	Avg. hot start ≤2sec Avg. cold start ≤35sec
others	Touch screen	1.54 inch
	Resolution	240*240
	Battery	3.8V/1500mAh lithium-polymer battery
	Standby time	>=72 hours (LTE & WIFI work; GPS sleeps) >8 hours (LTE & GPS work)
	Standby current	≤ 14mA (LTE works while GPS sleep)
	MIC	√
	SIM card	nano
	Speaker	√
	Charge voltage/current	5VDC/1000mA
	Charge port	USB type-C
	Operating temperature	-20°C~ 60°C
	Operating humidity	5%~95%, non-dense
	Storage temperature	-30°C ~75°C
	Dimensions	101.0(L)*62.0(W)*11.0(H)mm
Weight	81g	

Contact

Jimi Electronic Co., Ltd.

Add: 4/F, Building B, Gaoxinqi Industrial Park, Liuxian 1st Road, No.67 Bao'an District, Shenzhen

Tel: +86 755 6664 2520

Web: www.jimilab.com

Email: info@jimilab.com