

Description:

Atlanta W-Track is manufactured using the best quality raw materials and innovative technology by adept professionals. This tracker comes in various specifications, designs and sizes, in adherence with quality standards. Moreover, the provided tracker is rigorously tested by quality examiners on varied parameters, in order to deliver a flawless tracker to esteemed clients.

Specification:

- Power Requirement: 12 V to 36 V
- Normal operation temperature: -30 °C to 80 °C
- Restricted operation temperature: -40 °C to -30 °C and 80 °C to 85 °C
- Storage temperature: -45°C to 90°C
- Humidity: 5% to 95%

Feature:

- Less power consumption
- Compact design
- High operational fluency
- Combination of GSM/GPRS wireless network
- Easy to install or hide in the vehicle to perform tracking.
- Ideal application for vehicle tracking and equipment/assets monitoring.
- External DC power supply
- Configuration can be done via SMS commands
- Real-time GSM location monitoring on SMS
- Vehicle control with Immobilization
- Waterproof enclosure
- Inbuilt GSM antenna

GSM Module:

- Tri-Band GSM/GPRS 900/1800/1900MHz
- GPRS multi-slot class 10/8
- GPRS mobile station class B
- Class 4(2W @ 850/900 MHz)
- Baud Rate: 9600 bps

Description:

Atlanta W-Track is manufactured using the best quality raw materials and innovative technology by adept professionals. This tracker comes in various specifications, designs and sizes, in adherence with quality standards. Moreover, the provided tracker is rigorously tested by quality examiners on varied parameters, in order to deliver a flawless tracker to esteemed clients.

Specification:

- Power Requirement: 12 V to 36 V
- Normal operation temperature: -30 °C to 80 °C
- Restricted operation temperature: -40 °C to -30 °C and 80 °C to 85 °C
- Storage temperature: -45°C to 90°C
- Humidity: 5% to 95%

Feature:

- Less power consumption
- Compact design
- High operational fluency
- Combination of GSM/GPRS wireless network
- Easy to install or hide in the vehicle to perform tracking.
- Ideal application for vehicle tracking and equipment/assets monitoring.
- External DC power supply
- Configuration can be done via SMS commands
- Real-time GSM location monitoring on SMS
- Vehicle control with Immobilization
- Waterproof enclosure
- Inbuilt GSM antenna

GSM Module:

- Tri-Band GSM/GPRS 900/1800/1900MHz
- GPRS multi-slot class 10/8
- GPRS mobile station class B
- Class 4(2W @ 850/900 MHz)
- Baud Rate: 9600 bps